

Driver Flex CPM						DRIVER CLUBHEAD SPEED	DRIVER CLUBHEAD DISTANCE	
FULL SWING		3/4 SWING		HALF SWING				
								
FULL SWING		3/4 SWING		HALF SWING			YARDS	
195	WOMEN'S FLEX		215	215	SENIOR FLEX	215	< 75	<190
218	WOMEN'S FLEX	225	225	SENIOR FLEX		235	76 - 83	195 - 210
236	SENIOR FLEX	240	240	REGULAR FLEX		245	84 - 89	210 - 230
245	REGULAR FLEX		250	250	STIFF FLEX	255	90 - 96	231 - 245
255	STIFF FLEX		260			263	97 - 102	246 - 255
264	STIFF FLEX	265	265	EXTRA-STIFF FLEX		270	103 - 109	256 - 275
270	EXTRA-STIFF FLEX				275		110 <	>275

IRONS		IRONS		IRONS	
Graphite	50-80 g	Graphite/Steel	85-115 g	Steel	120+ g
WOODS		WOODS		WOODS	
Graphite	40-50 g	Graphite	55-70 g	Graphite	75+ g

Swing Speed 44 1/2"	Swing Speed 44 1/2"	Industry Flex Designation	PCS Equalizer Flex Value	CPM Driver	CPM 7 iron
Driver (mph)	Distance				
120+	250	X - Stiff	7.3-7.7	269-273	331-335
114-118	240		6.9-7.3	265-269	327-331
110-114	230		6.5-6.9	261-265	323-327
106-110	220	Stiff	6.1-6.5	257-261	319-323
102-106	210		5.7-6.1	253-257	315-319
98-102	200		5.3-5.7	249-253	311-315
94-98	190		4.9-5.3	245-249	307-311
90-94	180	Regular	4.5-4.9	241-245	303-307
86-90	170		4.1-4.5	237-241	299-303
82-86	160		3.7-4.1	233-237	295-299
78-82	150		3.3-3.7	229-233	291-295
74-78	144	Senior	2.9-3.3	225-229	287-291
70-74	135		2.5-2.9	221-225	283-297
66-70	130		2.1-2.5	217-221	279-283
62-66	125		1.7-2.1	213-217	275-279
57-62	120	Lite	1.2-1.7	208-213	270-275
53-57	100		0.8-1.2	204-208	266-270
49-53	100		0.4-0.8	200-204	262-266
45-49	<100		0.0-0.4	196-200	258-262